

topCLEAR Special

Washing machine for professional cleaning of glass up to 12 mm thickness

topCLEAR Special is the perfect washing machine for industrial glass processing, as long as no extreme glass thicknesses are processed. A particular advantage is the extremely easy access to the machine for user-friendly maintenance. topCLEAR Special can be individually configured to meet the needs of solar production and multi-shift operation.



Technical Data

	topCLEAR 13 Special 4/12	topCLEAR 16 Special 4/12
Max. processing height	1.3 m	1.6 m
Construction	Open at the top	Open at the top
Glass thickness	4 - 12 mm / 4 - 20 mm	
Minimum size	270 x 50 mm	
Length of the inlet table	1,400 mm (optional 2,000 mm) - modularly expandable	
Length of the outlet table	2,000 mm (optional 2,600 mm) - modularly expandable	
Angle of inclination	7° (+/- 1°)	
Transport height	600 mm (+/- 20 mm) / optional increase	
Number of brushes	4 brushes	
Transport speed	1 - 5 m/min	

Highlights

- All important machine components made from stainless steel
- Doors front- and rearside as maintenance entry
- Guards in polycarbonate behind the doors
- Individual water pump for each pair of brushes

Options

- Rollers with slip clutch
- AutoStart system for power saving
- Light panels on outlet side
- Pre-washing area with high pressure pump, separate tank
- Soft brushes frontside for soft coated glass



1

1 Optimal accessibility

- Doors front- and rearside for easy maintenance
- Plexiglas guards for inspection
- Additional noise reduction

2 Simple operation

- Ingenious - AutoStart system activates brushes, pump and ventilator only when needed (optional).



2